

WHAT IS CLAIMED IS:

1 1. A method in a signal processor for filtering samples in a digital signal,
2 the method comprising:
3 generating an approximate filtered sample as a function of less than four
4 samples of the digital signal;
5 generating a correction as a function of the less than four samples; and
6 generating a filtered sample by modifying the approximate filtered sample
7 with the correction.

1 2. The method of claim 1, wherein the less than four samples are only
2 two samples.

1 3. The method of claim 2, wherein the two samples are a first fixed-point
2 number, A, and a second fixed-point number, B, wherein generating the approximate filtered
3 sample includes calculating $(A+B+1) \gg 1$.

1 4. The method of claim 3, wherein the signal processor is a
2 microprocessor having an instruction for calculating the function $(X+Y+1) \gg 1$, and wherein
3 calculating $A+B+1 \gg 1$ is performed using the instruction.

1 5. The method of claim 4, wherein the microprocessor is an IntelTM
2 microprocessor with SSE or SSE2, and wherein the instruction is the PAVGB instruction.

1 6. The method of claim 4, wherein the microprocessor is an IntelTM
2 microprocessor with SSE or SSE2, and wherein the instruction is the PAVGW instruction.

1 7. The method of claim 3, wherein generating the approximate filtered
2 sample further includes calculating $(A + ((A+B+1) \gg 1) + 1) \gg 1$.

1 8. The method of claim 3, wherein generating the approximate filtered
2 sample further includes:

3 calculating $E = ((A+B+1) \gg 1) \ll S$;

4 calculating $F = ((A+B+1) \gg 1) \ll R$; and

5 calculating the approximate filtered sample as $E + F$;

6 wherein S and R are positive fixed-point numbers.

9. The method of claim 8, wherein generating the correction includes:
calculating $Q = \sim(A \oplus B)$;
masking Q with the number one;
calculating $G = Q \ll (S-1)$;
calculating $H = Q \ll (R-1)$; and
calculating the correction as $G + H$.

10. The method of claim 9, wherein generating the filtered sample includes:
calculating the filtered sample as the approximate filtered sample added with the correction; and
right-shifting the filtered sample by N-1 bits, wherein N is a positive fixed-point number.

11. The method of claim 3, wherein generating the approximate filtered sample further includes:
calculating $E = ((A+B+1) \gg 1) \gg (N-1-S)$;
calculating $F = ((A+B+1) \gg 1) \gg (N-1-R)$; and
adding E with F;
wherein N, S and R are positive fixed-point numbers, and wherein $N \geq S > R$.

12. The method of claim 11, wherein generating the correction includes:
calculating $Q = \sim(A \oplus B)$;
masking Q with the number one;
calculating $G = Q \gg (N-S)$;
calculating $H = Q \gg (N-R)$; and
calculating the correction as $G + H$.

13. The method of claim 12, wherein generating the filtered sample includes calculating the filtered sample as the approximate filtered sample added with the correction.

14. The method of claim 2, wherein the two samples are fixed-point numbers, and wherein generating the correction includes:
calculating the correction as the exclusive OR (XOR) of the two samples; and

masking the correction with the integer one.

15. The method of claim 14, wherein generating the correction further includes, prior to the masking step, generating a bit-wise complement of the correction.

16. The method of claim 2, wherein the two samples are fixed-point numbers A, B, and wherein generating the correction includes:
calculating the correction as $(A \oplus B)$ OR $(A \oplus (A+B \gg 1))$; and
masking the correction with the number one.

17. The method of claim 2, wherein the two samples are fixed-point numbers A, B, and wherein generating the correction includes:
calculating the correction as $(A \oplus (A+B \gg 1))$; and
bit-wise ANDing the correction with the number one.

18. The method of claim 1, wherein generating the filtered sample includes adding the correction to the approximate filtered sample.

19. The method of claim 1, wherein generating the filtered sample includes subtracting the correction from the approximate interpolated sample.

20. The method of claim 2, wherein the microprocessor is an IntelTM microprocessor with MMXTM/SSE, wherein the two samples are 8-bit fixed-point numbers, wherein the steps of generating the approximate filtered sample, generating the correction and generating the filtered sample include executing the instructions:

```
pxor      C_REG, A_REG ;  
pand      C_REG, CONST ;  
pavgb     A_REG, B_REG ;  
psubb     A_REG, C_REG ;
```

wherein A_REG is a register that initially includes one of the two samples, B_REG is a register that includes the other of the two samples, C_REG is a register that initially includes the other of the two samples, and CONST is a constant that includes the eight-bit number 0x01.

21. The method of claim 2, wherein the microprocessor is an IntelTM microprocessor with MMXTM/SSE, wherein the two samples are eight bit integers, wherein

3 the steps of generating the approximate filtered sample, generating the correction and
4 generating the filtered sample include executing the instructions:

```
5         pxor      C_REG, A_REG ;  
6         pandn     C_REG, CONST ;  
7         pavgb     A_REG, B_REG ;  
8         paddb     A_REG, C_REG ;
```

9 wherein A_REG is a register that initially includes one of the two samples,
10 B_REG is a register that includes the other of the two samples, C_REG is a register that
11 initially includes the other of the two samples, and CONST is a constant that includes the
12 eight-bit number 0x01.

1 22. The method of claim 1, wherein the less than four samples are only
2 three samples.

1 23. The method of claim 22, wherein the two samples are a first fixed-
2 point number, A, a second fixed-point number, B, and a third fixed-point number, C, wherein
3 generating the approximate filtered sample includes:

4 calculating $M = (A+B+1) \gg 1$;
5 calculating $N = (C+0+1) \gg 1$; and
6 calculating the approximate filtered sample as $X = (M+N+1) \gg 1$.

1 24. The method of claim 23, wherein generating the correction includes:
2 calculating the correction as $((A \oplus B) \text{AND}(C)) \text{OR}(M \oplus N)$; and
3 masking the correction with the number one.

1 25. The method of claim 23, wherein generating the correction includes:
2 calculating the correction as $(A \oplus B) \text{OR } C \text{ OR}(M \oplus N)$; and
3 masking the correction with the number one.

1 26. The method of claim 22, wherein the two samples are a first fixed-
2 point number, A, a second fixed-point number, B, and a third fixed-point number, C, wherein
3 generating the approximate filtered sample includes:

4 calculating $M = (B+C+1) \gg 1$; and
5 calculating the approximate filtered sample as $X = (A+M+1) \gg 1$.

1 27. The method of claim 26, wherein generating the correction includes:
2 calculating the correction as $A \oplus M$; and

3 masking the correction with the number one.

1 28. The method of claim 26, wherein generating the correction includes:
2 calculating the correction as $(B \oplus C) \text{ OR } (A \oplus M)$; and
3 masking the correction with the number one.

1 29. A method in a signal processor for filtering samples in a digital signal,
2 the method comprising:

3 generating an approximate filtered sample as a function of a first sample, A, a
4 second sample, B, a third sample, C, and a fourth sample, D, wherein A, B, C, and D are
5 fixed-point numbers;

6 generating a correction as $((A \oplus B) \text{ AND } (C \oplus D)) \text{ OR } (M \oplus N)$, wherein
7 $M = A + B + 1 \gg 1$ and $N = C + D + 1 \gg 1$;

8 masking the correction; and

9 generating a filtered sample by modifying the approximate filtered sample
10 with the correction.

1 30. The method of claim 29, wherein generating the approximate filtered
2 sample includes:

3 calculating $M = A + B + 1 \gg 1$;

4 calculating $N = C + D + 1 \gg 1$; and

5 calculating the approximate filtered sample as $M + N + 1 \gg 1$.

1 31. The method of claim 30, wherein the signal processor is a
2 microprocessor having an instruction for calculating the function $X + Y + 1 \gg 1$, wherein the
3 step of calculating M is performed using the instruction, wherein the step of calculating N is
4 performed using the instruction, and wherein the step of calculating the approximate filtered
5 sample is performed using the instruction.

1 32. The method of claim 31, wherein the microprocessor is an IntelTM
2 microprocessor with SSE or SSE2, and wherein the instruction is the PAVGB instruction.

1 33. The method of claim 31, wherein the microprocessor is an IntelTM
2 microprocessor with SSE or SSE2, and wherein the instruction is the PAVGW instruction.

1 34. The method of claim 29, wherein the microprocessor is an IntelTM
2 microprocessor with MMXTM/SSE, wherein the A, B, C, and D are eight bit fixed-point
3 numbers, wherein the steps of generating the approximate filtered sample, generating the
4 correction, masking the correction and generating the filtered sample include executing the
5 instructions:

```
6           pxor        A_REG, B_REG ;  
7           pxor        C_REG, D_REG ;  
8           pand        A_REG, C_REG ;  
9           pavgb       M_REG, B_REG ;  
10          pavgb       N_REG, D_REG ;  
11          movq        B_REG, M_REG ;  
12          pxor        B_REG, N_REG ;  
13          pand        B_REG, CONST ;  
14          pavgb       M_REG, N_REG ;  
15          psubb        M_REG, B_REG ;
```

16 wherein A_REG is a register that initially includes A, B_REG is a register that
17 initially includes B, C_REG is a register that initially includes C, D_REG is a register that
18 includes D, CONST is a constant that includes the eight-bit number 0x01, M_REG is a
19 register that initially includes A, and N_REG is a register that initially includes C.

1 35. A method in a signal processor for filtering samples in a digital signal,
2 the method comprising:

3 generating an approximate filtered sample as a function of a first sample, A, a
4 second sample, B, a third sample, C, and a fourth sample, D, wherein A, B, C, and D are
5 integers;

6 generating a correction as $(A \oplus B) \text{OR} (C \oplus D) \text{OR} (M \oplus N)$, wherein
7 $M = A + B + 1 \gg 1$ and $N = C + D + 1 \gg 1$;

8 masking the correction; and

9 generating a filtered sample by modifying the approximate filtered sample
10 with the correction.

1 36. The method of claim 35, wherein generating the approximate filtered
2 sample includes:

3 calculating $M = A + B + 1 \gg 1$;

4 calculating $N = C + D + 1 \gg 1$; and

5 calculating the approximate interpolated sample as $M + N + 1 \gg 1$.

1 37. The method of claim 36, wherein the signal processor is a
2 microprocessor having an instruction for calculating the function $X+Y+1 \gg 1$, wherein the
3 step of calculating M is performed using the instruction, wherein the step of calculating N is
4 performed using the instruction, and wherein the step of calculating the approximate filtered
5 sample is performed using the instruction.

1 38. The method of claim 37, wherein the microprocessor is an IntelTM
2 microprocessor with SSE or SSE2, and wherein the instruction is the PAVGB instruction.

1 39. The method of claim 37, wherein the microprocessor is an IntelTM
2 microprocessor with SSE or SSE2, and wherein the instruction is the PAVGW instruction.

1 40. The method of claim 35, wherein the microprocessor is an IntelTM
2 microprocessor with MMXTM/SSE, wherein the A, B, C, and D are eight bit numbers,
3 wherein the steps of generating the approximate filtered sample, generating the correction,
4 masking the correction and generating the filtered sample include executing the instructions:

5 pxor A_REG, B_REG ;
6 pxor C_REG, D_REG ;
7 por A_REG, C_REG ;
8 pavgb M_REG, B_REG ;
9 pavgb N_REG, D_REG ;
10 movq B_REG, M_REG ;
11 pxor B_REG, N_REG ;
12 pand B_REG, CONST ;
13 pavgb M_REG, N_REG ;
14 psubb M_REG, B_REG ;

15 wherein A_REG is a register that initially includes A, B_REG is a register that
16 initially includes B, C_REG is a register that initially includes C, D_REG is a register that
17 includes D, CONST is a constant that includes the eight-bit integer value one, M_REG is a
18 register that initially includes A, and N_REG is a register that initially includes C.

1 41. A method in a signal processor for filtering samples in a digital signal,
2 the method comprising:

3 generating an approximate filtered sample as a function of a first sample, A, a
4 second sample, B, a third sample, C, and a fourth sample, D, wherein A, B, C, and D are
5 fixed-point numbers;

6 generating a correction as $(A \oplus B) \text{OR} (C \oplus D) \text{OR} (M \oplus N)$, wherein
7 $M = A + B + 1 \gg 1$ and $N = C + D + 1 \gg 1$;
8 masking the correction; and
9 generating a filtered sample by modifying the approximate filtered sample
10 with the correction.

1 42. A method in a signal processor for filtering samples in a digital signal,
2 the method comprising:
3 generating $M1 = (A + B + 1) \gg 1$, wherein A and B are samples in the digital
4 signal;
5 generating $M2 = (C + D + 1) \gg 1$, wherein C and D are samples in the digital
6 signal;
7 generating $M3 = (E + F + 1) \gg 1$, wherein E and F are samples in the digital
8 signal;
9 generating $M4 = (G + H + 1) \gg 1$, wherein G and H are samples in the digital
10 signal;
11 generating $N1 = (M1 + (M3 \gg 1) + (M3 \gg 2)) \gg 2$;
12 generating $N2 = (M2 + (M2 \gg 1) + (M4 \gg 2)) \gg 2$; and
13 generating a filtered sample as $M1 + N1 - N2$.

1 43. A computer program product comprising:
2 a computer readable storage medium having computer program code
3 embodied therein for quantizing a digital signal, the computer program code comprising:
4 code for generating an approximate filtered sample as a function of less than
5 four samples of the digital signal;
6 code for generating a correction as a function of the less than four samples;
7 and
8 code for generating a filtered sample by modifying the approximate filtered
9 sample with the correction.

1 44. A system for filtering samples in a digital signal, the system
2 comprising:
3 a memory that stores samples in the digital signal; and
4 a processor coupled to the memory and operable to perform the steps of:

- 5 A) generating an approximate filtered sample as a function of less than
6 four samples of the digital signal;
7 B) generating a correction as a function of the less than four samples;
8 and
9 C) generating a filtered sample by modifying the approximate filtered
10 sample with the correction.

1 45. A computer program product comprising:
2 a computer readable storage medium having computer program code
3 embodied therein for quantizing a digital signal, the computer program code comprising:
4 code for generating an approximate filtered sample as a function of a first
5 sample, A, a second sample, B, a third sample, C, and a fourth sample, D, wherein A, B, C,
6 and D are fixed-point numbers;
7 code for generating a correction as $((A \oplus B) \text{AND} (C \oplus D)) \text{OR} (M \oplus N)$, wherein
8 $M = A + B + 1 \gg 1$ and $N = C + D + 1 \gg 1$;
9 code for masking the correction; and
10 code for generating a filtered sample by modifying the approximate filtered
11 sample with the correction.

1 46. A system for filtering samples in a digital signal, the system
2 comprising:
3 a memory that stores samples in the digital signal; and
4 a processor coupled to the memory and operable to perform the steps of:
5 A) generating an approximate filtered sample as a function of a first
6 sample, A, a second sample, B, a third sample, C, and a fourth
7 sample, D, wherein A, B, C, and D are fixed-point numbers;
8 B) generating a correction as $((A \oplus B) \text{AND} (C \oplus D)) \text{OR} (M \oplus N)$,
9 wherein $M = A + B + 1 \gg 1$ and $N = C + D + 1 \gg 1$;
10 C) masking the correction; and
11 D) generating a filtered sample by modifying the approximate filtered
12 sample with the correction.